

Super Seal™ Junior



Hand Held Induction Sealer

Prevent leaks, preserve freshness and provide tamper evidence with this portable induction cap sealer.

Super Seal™ Junior offers unprecedented sealing capabilities from a small footprint. Features include a digital sealing timer, missing foil indicator, as well as an electronic batch and foil counter.

**CREATES HERMETIC
INDUCTION SEALS**

**IDEAL FOR LABS AND SMALL
PRODUCTION RUNS**

SIMPLE SETUP & OPERATION

**POWERFUL SEALING WITH
PROFESSIONAL GRADE
COMPONENTS**

**CARRY CASE INCLUDED FOR
PORTABILITY**



**Innovative People.
Ensuring Your Sealing Success.**

+44 1296 330542 / www.enerconind.co.uk

What you need for induction cap sealing:

Materials: Cap with induction liners inserted, compatible bottle

Equipment: Enercon induction cap sealer including power supply and sealing head



How Induction Sealing Works - Pressure, heat and time

Your torqued cap ensures the induction liner is held firmly in place during the induction sealing process. When energised by the sealer's power supply, the sealing head induces current into the foil with its electromagnetic field. This current works with the natural electrical resistance of the foil to create heat. The heat melts the polymer coating on the bottom of the inner seal, forming a hermetic seal on the container.

How to use the Super Seal™ Jr

Simply plug in the Super Seal™ Junior and get ready to seal your first container. Set the sealing timer for your application. Less than one second is almost always enough and Enercon's experts will help you determine what's

best for your application. Centre the sealing head on the container's cap and press the trigger on the sealing head handle. The timer will count down to zero as power is applied into the cap to form the seal.



OPERATOR INTERFACE

Features

- Advanced circuitry and Enercon's well-proven and ultra-reliable sealing head design
- Maximum sealing power from a small footprint
- Standard sealing head seals cap diameters up to 83mm, with available sealing head capable of sealing cap diameters up to 120mm
- Seals flat and yorker cap styles
- Digital timer to ensure accurate sealing
- Missing Foil indicator
- Batch counter
- Easy hand held design



Specifications

	3" x 8.25" x 10.5" (76mm x 210mm x 267mm)
Weight	8 lbs. (3.6 kg)
Input	240 VAC, 50/60Hz

CARRYING CASE INCLUDED



+44 1296 330542 / www.enerconind.co.uk